



**TABEL FINISAJE INTERIOARE PARTER**

FINISAJE	INCAPERI	SUBSOL
Finisaje pereti	S-01-S-02-S-03S-04S-05S-06S-07S-08	TEHNIC
teraziola oticuzita + vopseala lavabila		
perete b.a. netedat		
Finisaje lavare		
teraziola oticuzita + vopseala lavabila		
Finisaje pardoseli		
gresie trafic intens, antiderapanta		
250x250x10mm; sapa ciment		
stare grosie, h=10cm		
sapa ciment necalzita		
placa b.a. nelinsala		

**SUBSOL**

Indicativ	Funciune	Suprafata	Perimetru
S-41	CASA SCARI	10.90 mp	113.80 m
S-42	CORIDOR	55.30 mp	14.00 m
S-43	CAMERA FRIGORIFICA	7.20 mp	
S-44	DEPOZIT SEMPREPARATE	8.28 mp	10.80 m
S-45	DEPOZIT LEG. SI FRUCTE	13.20 mp	13.20 m
S-46	CENTRALA TERMICA	44.42 mp	28.71 m
S-47	CAM. REZ. APA INCENDIU	17.93 mp	17.97 m
S-48	ADAP. PROTECTIE CIVILA	18.50 mp	37.40 m
SUBSOL		360.00 mp	
TEHNIC			
AU. SUBSOL FUNCTIONAL			210.76 mp
AU. CURTE DE LUMINA			20.00 mp
AU. SUBSOL TEHNIC			393.00 mp

**LEGENDA**

- INCHIDERI SUBSOL:
- pereti b.a. gr. = 30cm + hidroizolatie verticale membrana bituminoasa 2mm
- +protectie hidroizolatie membrana cu crampoane DELTA MS
- COMPARTIMENTARI INTERIOARE:
- pereti zidarie de caramida GV/290x240x138mm, gr. totala = 25/14cm

**VERIFICATOR EXPERT**

PRISAROM Engineering SA Str. Hristo Bolev 11, Sect. 3 Bucuresti, Romania C.F. 0756004	PROIECTANT ING. PICTOR TATARSCU	PROIECT nr. 1414/2012
Specificatie	Scara	1:50
DESEINAT	DE CLADIRE	PLAN SUBSOL
VERIFICAT	2012	

